

Frequency Synchronization and Multi-stability in Power Grids

Saber Jafarpour



Center for Control, Dynamical Systems & Computation
University of California at Santa Barbara

California Institute of Technology

May 11, 2021

Acknowledgment



Francesco Bullo
UCSB



Elizabeth Huang
UCSB



Kevin Smith
UCSB

SJ and Francesco Bullo. [Synchronization of Kuramoto Oscillators via Cutset Projections](#). IEEE Transactions on Automatic Control, 2019.

SJ and Elizabeth Y. Huang and Kevin D. Smith and Francesco Bullo. [Flow and Elastic Networks on the \$n\$ -torus: Geometry, Analysis, and Computation](#). SIAM Review, accepted, 2021.

Introduction: Large-scale Nonlinear Networks



Power grids



Brain neural network



Transportation network

Nonlinearity:

- Multiple equilibria
- Transient stability
- Cluster synchronization

Large-scale:

- Stochastic
- Distributed

- “... As [power] systems become more heavily loaded, nonlinearities play an increasingly important role in power system behavior ... ” [I. Hiskens,1995]
- “... in Oahu, Hawaii, at least 800,000 micro-inverters interconnect photovoltaic panels to the grid... ” [IEEE Spectrum, 2015]

Frequency Synchronization and Multi-stability in Power Grids

- oscillator networks and power grids
- transition from frequency synchronization to incoherency
 - [cutset projection](#)
 - [sufficient synchronization conditions](#)
- multiplicity of equilibria
 - [winding cells](#)
 - [contractive iterations for computing equilibria](#)

Phenomenon #1: Transition from sync to incoherency

Frequency synchronization:

- Frequency synchronization is crucial for functionality and operation of power grids.
- Power electronic devices are designed to work at 60 Hz in the US (50 Hz in Europe)
- Increase in the network supply/demand and failure of lines can cause transition to incoherency.
- Loss of frequency synchronization leads to blackouts.





Figure: Southern California Blackout 2011– the gray area is the islanded part of the grid

Phenomenon #2: Multi-stable power flows

Theoretical observation:

- Multiple stable operating points exist in power networks

[A. Korsak, On the question of uniqueness of stable load-flow solutions, 1972]




Practical observations:

- Undesirable power flows around loops (Fig. (a): Lake Erie loop in the 2009 US blackout)
- Dramatic change in power flow patterns before and after line trip (Fig. (b): Sammis–Star Trip in the 2003 US blackout)



(a)



(b)

Model: Coupled Oscillators Network

Pendulum clocks: “an odd kind of sympathy”

[C. Huygens, *Horologium Oscillatorium*, 1673]

Models for coupled oscillators:

[A. T. Winfree, 1967 and Y. Kuramoto 1975]

Model: Coupled Oscillators Network

Pendulum clocks: “an odd kind of sympathy”

[C. Huygens, *Horologium Oscillatorium*, 1673]


Models for coupled oscillators:

[A. T. Winfree, 1967 and Y. Kuramoto 1975]

Kuramoto Model

- 1 **n-oscillators** with phases θ_i ,
- 2 with natural frequencies $\omega_i \in \mathbb{R}$,
- 3 **coupling** with strength $a_{ij} = a_{ji}$.

$$\dot{\theta}_i = \omega_i - \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j).$$




① generators ■ and inverters and loads ●

Model: Active Power Dynamics

- ① generators ■ and inverters and loads ●
- ② physics:
 - ① Kirchhoff and Ohm laws
 - ② **quasi-sync**: voltage and phase V_i, θ_i
active power p_i

Model: Active Power Dynamics

- 1 generators ■ and inverters and loads ●
- 2 physics:
 - 1 Kirchhoff and Ohm laws
 - 2 **quasi-sync**: voltage and phase V_i, θ_i
active power p_i
- 3 simplifying assumptions:
 - 1 lossless and inductive lines with admittances Y_{ij}
 - 2 decoupling of phase and voltage dynamics



New England IEEE 39-bus

Model: Active Power Dynamics

Structure-Preserving Model [A. Bergen & D. Hill, 1981]:

Active Power Dynamics

$$\text{Generators:} \quad M_i \ddot{\theta}_i + D_i \dot{\theta}_i = p_i - \sum_j a_{ij} \sin(\theta_i - \theta_j)$$

$$\text{Inverters:} \quad \Lambda_i \dot{\theta}_i = p_i - \sum_j a_{ij} \sin(\theta_i - \theta_j)$$

$$\text{Loads:} \quad \tau_i \dot{\theta}_i = p_i - \sum_j a_{ij} \sin(\theta_i - \theta_j)$$

where

$$\text{Active power capacity of line } (i, j): \quad a_{ij} = |Y_{ij}| V_i V_j$$

Model: Active Power Dynamics

Structure-Preserving Model [A. Bergen & D. Hill, 1981]:

Active Power Dynamics

$$\text{Generators:} \quad M_i \ddot{\theta}_i + D_i \dot{\theta}_i = p_i - \sum_j a_{ij} \sin(\theta_i - \theta_j)$$

$$\text{Inverters:} \quad \Lambda_i \dot{\theta}_i = p_i - \sum_j a_{ij} \sin(\theta_i - \theta_j)$$

$$\text{Loads:} \quad \tau_i \dot{\theta}_i = p_i - \sum_j a_{ij} \sin(\theta_i - \theta_j)$$

where

$$\text{Active power capacity of line } (i, j): \quad a_{ij} = |Y_{ij}| V_i V_j$$

Synchronization = sync'd frequencies & bounded active power flows

$$\dot{\theta}_i = \omega_{\text{sync}}, \forall \text{ bus } i \quad \& \quad |\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \forall \text{ line } (i, j)$$

Synchronization = Equilibrium point = Stable operating point

$$p_i = \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j), \quad \forall \text{ bus } i,$$

$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j)$$

Key questions

Given the network and the power profile:

Q1: does there exist a **stable operating point**?

Q2: is the stable operating point **unique**?



Q3: how to measure the **robustness** of the synchronization?

Phenomenon #1: Transition from sync to incoherency


Revisited

Q1: Existence of an operating point:

$$\dot{\theta}_i = p_i - \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j)$$



$P = 1$





$P = 2.5$

Phenomenon #1: Transition from sync to incoherency


Revisited

Q1: Existence of an operating point:

$$\dot{\theta}_i = p_i - \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j)$$



$P = 1$



$P = 2.5$

- sync threshold : “power transmission” vs. “coupling”
- quantify: “power transmission” < “coupling”
- as a function of network parameters

Weighted undirected graph with n nodes and m edges:

Incidence matrix: $n \times m$ matrix B s.t. $(B^\top p)_{(ij)} = p_i - p_j$

Edge weight matrix: $m \times m$ diagonal matrix \mathcal{A}

Laplacian matrix: $L = B\mathcal{A}B^\top$

Operating point:

$$p = B\mathcal{A} \sin(B^\top \theta)$$

Algebraic connectivity:

$\lambda_2(L) =$ second smallest eig of L

= notion of connectivity and coupling

Given a network and p , does there exist angles?

$$p = B\mathcal{A} \sin(B^\top \theta),$$
$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j).$$

synchronization arises if

power transmission < **coupling strength**

Given a network and p , does there exist angles?

$$p = BA \sin(B^\top \theta),$$
$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j).$$

synchronization arises if

power transmission < **coupling strength**

Equilibrium angles (neighbors within $\pi/2$ arc) exist if

$$\|B^\top p\|_2 < \sin(\gamma)\lambda_2(L) \quad \text{for all graphs} \quad (\text{Old 2-norm T})$$
$$(\text{Old } \infty\text{-norm T})$$

Given a network and p , does there exist angles?

$$p = BA \sin(B^\top \theta),$$
$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j).$$

synchronization arises if



power transmission < **coupling strength**

Equilibrium angles (neighbors within $\pi/2$ arc) exist if

$$\|B^\top p\|_2 < \sin(\gamma) \lambda_2(L) \quad \text{for all graphs} \quad (\text{Old 2-norm T})$$



$$\|B^\top L^\dagger p\|_\infty < \sin(\gamma) \quad \text{for trees, complete} \quad (\text{Old } \infty\text{-norm T})$$

Novel: algebraic potential theory



$$\underbrace{\mathbb{R}^m}_{\text{edge space}} = \underbrace{\text{Im}(B^T)}_{\text{cutset space}} \oplus \underbrace{\text{Ker}(BA)}_{\text{weighted cycle space}}$$

Novel: algebraic potential theory





$$\underbrace{\mathbb{R}^m}_{\text{edge space}} = \underbrace{\text{Im}(B^\top)}_{\text{cutset space}} \oplus \underbrace{\text{Ker}(BA)}_{\text{weighted cycle space}}$$

$$\underbrace{\mathcal{P} = B^\top L^\dagger BA}_{\text{cutset projection}}$$

= oblique projection onto $\text{Im}(B^\top)$

parallel to $\text{Ker}(BA)$

Novel: algebraic potential theory



$$\underbrace{\mathbb{R}^m}_{\text{edge space}} = \underbrace{\text{Im}(B^\top)}_{\text{cutset space}} \oplus \underbrace{\text{Ker}(BA)}_{\text{weighted cycle space}}$$

$$\underbrace{\mathcal{P} = B^\top L^\dagger BA}_{\text{cutset projection}}$$

= oblique projection onto $\text{Im}(B^\top)$

parallel to $\text{Ker}(BA)$

- 1 if G acyclic, then $\mathcal{P} = I_m$
- 2 if G unweighted, then \mathcal{P} is an orthogonal projection
- 3 if $R_{\text{eff}} \in \mathbb{R}^{n \times n}$ are effective resistances, then $\mathcal{P} = -\frac{1}{2}B^\top R_{\text{eff}}BA$

Rewriting the equilibrium equation

Find sufficient conditions on B, \mathcal{A}, p s.t. there exists a solution θ to:

$$p = B\mathcal{A}\sin(B^\top\theta),$$

$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j).$$

Rewriting the equilibrium equation

Find sufficient conditions on B, \mathcal{A}, p s.t. there exists a solution θ to:

$$p = B\mathcal{A}\sin(B^\top\theta),$$
$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j).$$

Key idea: Node vs. Edge

$$p = B\mathcal{A}\sin(B^\top\theta)$$

Node balance eq. \mathbb{R}^n



$$B^\top L^\dagger p = \mathcal{P}\sin(B^\top\theta)$$

Edge balance eq. \mathbb{R}^m

Rewriting the equilibrium equation

Find sufficient conditions on B, \mathcal{A}, p s.t. there exists a solution θ to:

$$p = B\mathcal{A}\sin(B^\top\theta),$$
$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i,j).$$

Key idea: Node vs. Edge

$$p = B\mathcal{A}\sin(B^\top\theta) \quad \text{Node balance eq. } \mathbb{R}^n$$



$$B^\top L^\dagger p = \mathcal{P}\sin(B^\top\theta) \quad \text{Edge balance eq. } \mathbb{R}^m$$

- **Edge variables:** $x = B^\top\theta$ and $z = B^\top L^\dagger p$

Find sufficient conditions on $z \in \text{Im}(B^\top)$ s.t. there exists solution x to:

$$z = \mathcal{P}\sin(x) = \mathcal{P}[\text{sinc}(x)]x$$

Brouwer's Fixed-Point: A unifying theorem

- 2 look for $x \in \mathcal{B}_q(\gamma) = \{x \mid \|x\|_q \leq \gamma\}$ solving

$$\mathcal{P}[\text{sinc}(x)]x = z \quad \iff \quad x = (\mathcal{P}[\text{sinc}(x)])^{-1}z =: h(x)$$

Brouwer's Fixed-Point: A unifying theorem

- 2 look for $x \in \mathcal{B}_q(\gamma) = \{x \mid \|x\|_q \leq \gamma\}$ solving

$$\mathcal{P}[\text{sinc}(x)]x = z \iff x = (\mathcal{P}[\text{sinc}(x)])^{-1}z =: h(x)$$

- 3 define **min amplification factor** of $\mathcal{P}[\text{sinc}(x)] : \text{Im}(B^\top) \rightarrow \text{Im}(B^\top)$

$$\alpha_q(\gamma) := \min_{\|x\|_q \leq \gamma} \min_{\|y\|_q=1} \|\mathcal{P}[\text{sinc}(x)]y\|_q$$

Brouwer's Fixed-Point: A unifying theorem

- 2 look for $x \in \mathcal{B}_q(\gamma) = \{x \mid \|x\|_q \leq \gamma\}$ solving

$$\mathcal{P}[\text{sinc}(x)]x = z \iff x = (\mathcal{P}[\text{sinc}(x)])^{-1}z =: h(x)$$

- 3 define **min amplification factor** of $\mathcal{P}[\text{sinc}(x)] : \text{Im}(B^\top) \rightarrow \text{Im}(B^\top)$

$$\alpha_q(\gamma) := \min_{\|x\|_q \leq \gamma} \min_{\|y\|_q=1} \|\mathcal{P}[\text{sinc}(x)]y\|_q$$

$$\|z\|_q \leq \gamma \alpha_q(\gamma) \implies h \text{ satisfies Brouwer on } \mathcal{B}_q(\gamma)$$

Brouwer's Fixed-Point: A unifying theorem

Equilibrium angles (neighbors within γ arc) exist if, in some q -norm,

$$\|B^\top L^\dagger p\|_q \leq \gamma \alpha_q(\gamma) \quad \text{for all graphs} \quad (\text{New } q\text{-norm } T)$$

$$\alpha_q(\gamma) := \min \text{amplification factor of } \mathcal{P}[\text{sinc}(x)]$$

Brouwer's Fixed-Point: A unifying theorem

Equilibrium angles (neighbors within γ arc) exist if, in some q -norm,

$$\|B^\top L^\dagger p\|_q \leq \gamma \alpha_q(\gamma) \quad \text{for all graphs} \quad (\text{New } q\text{-norm } T)$$

$$\alpha_q(\gamma) := \min \text{amplification factor of } \mathcal{P}[\text{sinc}(x)]$$

- **Caveat:** $\alpha_q(\gamma)$ requires solving a non-convex optimization problem!

Brouwer's Fixed-Point: A unifying theorem

Equilibrium angles (neighbors within γ arc) exist if, in some q -norm,

$$\|B^\top L^\dagger p\|_q \leq \gamma \alpha_q(\gamma) \quad \text{for all graphs} \quad (\text{New } q\text{-norm } T)$$

$$\alpha_q(\gamma) := \min \text{amplification factor of } \mathcal{P}[\text{sinc}(x)]$$

- **Caveat:** $\alpha_q(\gamma)$ requires solving a non-convex optimization problem!
- Algebraic manipulation \implies lower bound $\alpha_q(\gamma)$.

Brouwer's Fixed-Point: A unifying theorem

Equilibrium angles (neighbors within γ arc) exist if, in some q -norm,

$$\|B^\top L^\dagger p\|_q \leq \gamma \alpha_q(\gamma) \quad \text{for all graphs} \quad (\text{New } q\text{-norm } T)$$

$$\alpha_q(\gamma) := \min \text{amplification factor of } \mathcal{P}[\text{sinc}(x)]$$

- **Caveat:** $\alpha_q(\gamma)$ requires solving a non-convex optimization problem!
- Algebraic manipulation \implies lower bound $\alpha_q(\gamma)$.

Brouwer's Fixed-Point: A unifying theorem

Equilibrium angles (neighbors within γ arc) exist if, in some q -norm,

$$\|B^\top L^\dagger p\|_q \leq \gamma \alpha_q(\gamma) \quad \text{for all graphs} \quad (\text{New } q\text{-norm } T)$$


$$\alpha_q(\gamma) := \min \text{amplification factor of } \mathcal{P}[\text{sinc}(x)]$$

- **Caveat:** $\alpha_q(\gamma)$ requires solving a non-convex optimization problem!
- Algebraic manipulation \implies lower bound $\alpha_q(\gamma)$.

For $q = \infty$, the new test for all graphs

$$\|B^\top L^\dagger p\|_\infty \leq g(\|\mathcal{P}\|_\infty) \quad (\text{New } \infty\text{-norm } T)$$

Function g is strictly decreasing



$$g : [1, \infty) \rightarrow [0, 1]$$

$$g(x) = \frac{y(x) + \sin(y(x))}{2} - x \frac{y(x) - \sin(y(x))}{2} \Big|_{y(x) = \arccos\left(\frac{x-1}{x+1}\right)}$$

Comparison of synchronization tests

K_C = critical coupling of Kuramoto model, computed via MATLAB *fsolve* K_T = smallest value of scaling factor for which test T fails

Test Case	Critical ratio K_T/K_C			
	Old 2-norm	New ∞ -norm $g(\ \mathcal{P}\ _\infty)$	Old ∞ -norm Approx.test	New ∞ -norm $\alpha_\infty(\pi/2)$
IEEE 9	16.54 %	73.74 %	92.13 %	85.06 % [†]
IEEE RTS 24	3.86 %	53.44 %	89.48 %	89.48 % [†]
New England 39-bus	2.97 %	67.57 %	100 %	100 % [†]
IEEE 118	0.29 %	43.70 %	85.95 %	— [*]
IEEE 300	0.20 %	40.33 %	99.80 %	— [*]
Polish 2383	0.11 %	29.08 %	82.85 %	— [*]

[†] *fmincon* has been run for 100 randomized initial phase angles.

^{*} *fmincon* does not converge.

Old 2-norm:

$$\|B^T p\|_2 \leq \sin(\gamma) \lambda_2(L)$$

New ∞ -norm:

$$\|B^T L^\dagger p\|_\infty \leq g(\|\mathcal{P}\|_\infty)$$

Old ∞ -norm Approx.:

$$\|B^T L^\dagger p\|_\infty \leq \sin(\gamma)$$

New ∞ -norm:


$$\|B^T L^\dagger p\|_\infty \leq \frac{\pi}{2} \alpha_\infty\left(\frac{\pi}{2}\right)$$

Phenomenon #2: Multi-stable power flows

Revisited


Q2: Is the operating point unique?

$$\dot{\theta}_i = p_i - \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j)$$




$$a_{ij} = 1$$

$$P = 1/4$$



$$\theta_0 = [-1, 1, -2, 0, 1.5, 0.5]^T$$




$$\theta_0 = [0, 1.2, 2.2, 3.9, 4.8, 1]^T$$

Phenomenon #2: Multi-stable power flows

Revisited


Q2: Is the operating point unique?

$$\dot{\theta}_i = p_i - \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j)$$




$$a_{ij} = 1$$

$$P = 1/4$$



$$\theta_0 = [-1, 1, -2, 0, 1.5, 0.5]^T$$



$$\theta_0 = [0, 1.2, 2.2, 3.9, 4.8, 1]^T$$

- multi-stable sync : “cycle structure” and “state space”
- quantify: “cycle structure” vs “multi-stable sync”

Key question

How to localize stable operating points?

Winding number


Algebraic graph theory on n -torus

Key question

How to localize stable operating points?


Winding number

Nodal variables in \mathbb{R}^3



$$\sum_{i=1}^3 \overbrace{(x_i - x_{i+1})}^{\text{distance in } \mathbb{R}} = 0.$$

Nodal variables in \mathbb{T}^3



$$\sum_{i=1}^3 \overbrace{(\theta_i - \theta_{i+1})}^{\text{distance in } \mathbb{S}} = 2\pi w_\sigma(\theta),$$

$w_\sigma(\theta) \in \mathbb{Z}$, winding number

Winding partition of the n -torus

Winding vectors and Kirchhoff angle law

Winding vector

Given a graph G with a cycle basis $\Sigma = \{\sigma_1, \dots, \sigma_{m-n+1}\}$ and $\theta \in \mathbb{T}^n$.

Winding vector: $\mathbf{w}_\Sigma(\theta) = [w_{\sigma_1}(\theta), \dots, w_{\sigma_{m-n+1}}(\theta)]^\top$

Theorem: Kirchhoff angle law on \mathbb{T}^n

$$w_\sigma(\theta) = 0, \pm 1, \dots, \pm \lfloor n_\sigma/2 \rfloor$$

$\implies \mathbf{w}_\Sigma(\theta)$ is piecewise constant,
 $\mathbf{w}_\Sigma(\theta)$ takes value in a finite set



Winding partition of the n -torus

Winding cells


Winding cells: equivalence classes

Given a graph G with a cycle basis Σ . For every $\mathbf{u} \in \mathbb{Z}^{m-n+1}$


$$(\text{Winding cell } \mathbf{u}) = \text{all } \theta \in \mathbb{T}^n \text{ s.t. } \mathbf{w}_\Sigma(\theta) = \mathbf{u}.$$



$\mathbf{u} = -1$



$\mathbf{u} = 0$





$\mathbf{u} = +1$


Theorem: Winding partition of n -torus

$$\mathbb{T}^n = \bigcup_{\mathbf{u} \in \mathbb{Z}^{m-n+1}} (\text{Winding cell } \mathbf{u})$$


Properties of the winding partition



$\mathbf{u} = -1$



$\mathbf{u} = 0$




$\mathbf{u} = +1$

- each winding cell is connected
- each winding cell is invariant under rotation
- **bijection**: winding cell \longleftrightarrow convex polytope

$$\|B^\top \theta - 2\pi C_\Sigma^\dagger \mathbf{u}\|_\infty < \pi.$$

C_Σ is the cycle-edge incidence matrix




At-most uniqueness in winding cells

Multi-stability

Given topology, admittances, and injections

$$p_i = \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j), \quad \forall \text{ bus } i$$

$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j)$$




At-most uniqueness in winding cells

Multi-stability

Given topology, admittances, and injections

$$p_i = \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j), \quad \forall \text{ bus } i$$

$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j)$$



Theorem: At-most-uniqueness and extensions


At-most uniqueness in winding cells

Multi-stability

Given topology, admittances, and injections

$$p_i = \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j), \quad \forall \text{ bus } i$$

$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j)$$



Theorem: At-most-uniqueness and extensions

- 1 each winding cell has at-most-unique equilibrium with $\Delta\theta \leq \gamma$


At-most uniqueness in winding cells

Multi-stability

Given topology, admittances, and injections

$$p_i = \sum_{j=1}^n a_{ij} \sin(\theta_i - \theta_j), \quad \forall \text{ bus } i$$

$$|\theta_i - \theta_j| \leq \gamma < \frac{\pi}{2}, \quad \forall \text{ line } (i, j)$$






Theorem: At-most-uniqueness and extensions

- 1 each winding cell has at-most-unique equilibrium with $\Delta\theta \leq \gamma$
- 2 equilibrium loop flow increases monotonically wrt winding number

At-most uniqueness in winding cells

Special topologies



- **Complete graph:** cycle basis of length 3 \implies at most one equilibrium
- **Complete bipartite:** cycle basis of length 4 \implies at most one equilibrium
- **Rectangular grid:** cycle basis of length 4 \implies at most one equilibrium

Iterations for normalized power flows

$$\eta^{(k+1)} = \eta^{(k)} - \cos(\gamma)(I_n - \mathcal{P})(\text{asin}(\eta^{(k)}) - 2\pi C_{\Sigma}^{\dagger} \mathbf{u}).$$

- Start from $\eta^{(0)} = \mathcal{A}^{-1} B^{\top} L^{\dagger} p$
- The sequence is **contractive** and always converges (to a vector η^*)
- **If** $\|\eta^*\|_{\infty} > \sin(\gamma)$: no stable equilibrium point in winding cell \mathbf{u} .
- **If** $\|\eta^*\|_{\infty} \leq \sin(\gamma)$: one stable equilibrium point in winding cell \mathbf{u} ;

$$\theta^* = L^{\dagger} B \mathcal{A}(\text{asin}(\eta^*) - 2\pi C_{\Sigma}^{\dagger} \mathbf{u})$$

- geometry of cutset projection operator
- family of sufficient sync conditions
- partition of n -torus based on winding vector
- localize the equilibrium points using winding cells

- close the gap between sufficient and necessary conditions
 - use suitable optimization algorithms to compute min amplification factor.
- region of attraction of stable equilibrium points
 - design suitable Lyapunov functions which can ensure convergence with transient guarantees
- generalizations to other oscillator models.
 - extension to multi-stability of state-space coupled oscillators such as FitzHugh–Nagumo